

## UHD55

4K UHD home entertainment and gaming projector









- 4K UHD resolution HDR and HLG compatible
- Lights on viewing 3600 ANSI lumens
- Supports 1080p 240Hz for smooth gaming and an input lag of 4ms
- Easy installation 1.3x zoom and vertical lens shift



.

## **Specifications**

The following specifications are prelir	
	minary and subject to change without notice
Display/image	
Display technology	DLP™
Resolution	UHD (3840x2160)
Brightness	3,600 lumens
Contrast ratio	1,200,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
Keystone correction -	+/-40°
horizontal	77 10
Keystone correction - vertical	+/-40°
Displayable colours (millions)	1073.4
Horizontal scan rate	31 ~ 135Khz
Vertical scan rate	24 ~ 120Hz
Uniformity	75%
Screen size	0.87m ~ 7.68m (34.1" ~ 302.4") diagonal
Lamp info	
Light source type	Lamp
Lamp watts	240
Lamp life hours (up to)	4000 (Bright), 15000 (Dynamic), 10000 (Eco)
Optical	
Throw ratio	1.21:1 ~ 1.59:1
Projection distance	1.2m - 8.1m / 47.24" - 318.9"
Zoom	1.3
	Manual
Zoom type	
Focal length	12.81 ~ 16.74
Lens shift	Vertical +10%
Native offset	105%
Connectivity	
Connections	Inputs 2 x HDMI 2.0, 1 x VGA (YPbPr/RGB), 1 x Audio
	3.5mm
	Outputs 1 x Audio 3.5mm, 1 x S/PDIF, 1 x USB-A power
	1.5A
	1.5A  Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V
General	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V
General	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45
Noise level (typical)	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45
Noise level (typical) Noise level (max)	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45  26dB 28dB
Noise level (typical)	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45  26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA,
Noise level (typical) Noise level (max) PC compatibility	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45  26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
Noise level (typical) Noise level (max)	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45  26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz),
Noise level (typical) Noise level (max) PC compatibility 2D compatibility	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45  26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz)
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45  26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45  26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45  26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45  26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese,
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45  26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D security OSD / display languages	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45  26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional)
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45  26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D security OSD / display languages	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45  26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional)
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45  26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Noise level (typical) Noise level (max) PC compatibility  2D compatibility  3D compatibility  3D Security OSD / display languages  Operating conditions Remote control	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45  26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Attitude 3000m Backlit home remote
Noise level (typical) Noise level (max) PC compatibility  2D compatibility  3D compatibility  3D Security OSD / display languages  Operating conditions Remote control Speaker count	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45  26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1
Noise level (typical) Noise level (max) PC compatibility  2D compatibility  3D compatibility  3D Security OSD / display languages  Operating conditions Remote control Speaker count Watts per speaker	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45  26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45  26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlith home remote 1 10W AC power cord
Noise level (typical) Noise level (max) PC compatibility  2D compatibility  3D compatibility  3D Security OSD / display languages  Operating conditions Remote control Speaker count Watts per speaker	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45  26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W AC power cord Remote control inc CR2025 battery
Noise level (typical) Noise level (max) PC compatibility  2D compatibility  3D compatibility  3D Security OSD / display languages  Operating conditions Remote control Speaker count Watts per speaker	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45  26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W AC power cord Remote control inc CR2025 battery Quick start user manual
Noise level (typical) Noise level (max) PC compatibility  2D compatibility  3D compatibility  3D Security OSD / display languages  Operating conditions Remote control Speaker count Watts per speaker In the box	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45  26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W AC power cord Remote control inc CR2025 battery Quick start user manual WUSB wireless adapter
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45  26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W AC power cord Remote control inc CR2025 battery Quick start user manual WUSB wireless adapter
Noise level (typical) Noise level (max) PC compatibility  2D compatibility  3D compatibility  3D Security OSD / display languages  Operating conditions Remote control Speaker count Watts per speaker In the box  Input lag  Power Power	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45  26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlith home remote 1 10W AC power cord Remote control inc CR2025 battery Quick start user manual WUSB wireless adapter 4.40ms
Noise level (typical) Noise level (max) PC compatibility  2D compatibility  3D compatibility  3D compatibility  3D Security OSD / display languages  Operating conditions Remote control Speaker count Watts per speaker In the box  Input lag Power Power supply Power consumption (standby)	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45  26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W AC power cord Remote control inc CR2025 battery Quick start user manual WUSB wireless adapter 4.40ms  100 ~ 240V, 50 ~ 60Hz 0.5W
Noise level (typical) Noise level (max) PC compatibility  2D compatibility  3D compatibility  3D Security OSD / display languages  Operating conditions Remote control Speaker count Watts per speaker In the box  Input lag Power Power Supply Power consumption (standby) Power consumption (min)	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45  26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W AC power cord Remote control inc CR2025 battery Quick start user manual WUSB wireless adapter 4.40ms  100 ~ 240V, 50 ~ 60Hz 0.5W 220W
Noise level (typical) Noise level (max) PC compatibility  2D compatibility  3D compatibility  3D Security OSD / display languages  Operating conditions Remote control Speaker count Watts per speaker In the box  Input lag Power Power Supply Power consumption (standby) Power consumption (min) Power consumption (max)	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45  26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W AC power cord Remote control inc CR2025 battery Quick start user manual WUSB wireless adapter 4.40ms  100 ~ 240V, 50 ~ 60Hz 0.5W
Noise level (typical) Noise level (max) PC compatibility  2D compatibility  3D compatibility  3D Security OSD / display languages  Operating conditions Remote control Speaker count Watts per speaker In the box  Input lag Power Power supply Power consumption (standby) Power consumption (min) Power consumption (max)  Weight and dimensions	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45  26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Attitude 3000m Backlit home remote 1 10W AC power cord Remote control inc CR2025 battery Quick start user manual WUSB wireless adapter 4.40ms  100 ~ 240V, 50 ~ 60Hz 0.5W 220W 320W
Noise level (typical) Noise level (max) PC compatibility  2D compatibility  3D compatibility  3D Security OSD / display languages  Operating conditions Remote control Speaker count Watts per speaker In the box  Input lag Power Power supply Power consumption (standby) Power consumption (min) Power consumption (max)  Weight and dimensions Dimensions (W x D x H)	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45  26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W AC power cord Remote control inc CR2025 battery Quick start user manual WUSB wireless adapter 4.40ms  100 ~ 240V, 50 ~ 60Hz 0.5W 220W 320W
Noise level (typical) Noise level (max) PC compatibility  2D compatibility  3D compatibility  3D Security OSD / display languages  Operating conditions Remote control Speaker count Watts per speaker In the box  Input lag Power Power supply Power consumption (standby) Power consumption (min) Power consumption (max)  Weight and dimensions	Control 1 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45  26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Attitude 3000m Backlit home remote 1 10W AC power cord Remote control inc CR2025 battery Quick start user manual WUSB wireless adapter 4.40ms  100 ~ 240V, 50 ~ 60Hz 0.5W 220W 320W