

# ZW410UST

Compact eco-friendly ultra short throw projector



- **Bright WXGA projector - 4000 lumens**
- **Ultra short throw lens - 100" image from less than half a metre away**
- **Ultimate control - Crestron, Extron, AMX, PJ-Link and Telnet LAN commands**
- **External power supply - More reliability, portability and energy efficiency**

The ZW410UST is one of Optoma's most compact and hassle-free WXGA DuraCore laser projectors to date. Designed for maintenance-free continuous operation, this 4,000-lumen projector delivers powerful image performance with flexible installation features and extensive connectivity options in a sleek, compact form factor.

Installation and setup are simple with four corner adjustment and the added benefit of an external power supply, offering more reliability, portability and energy efficiency.



## Specifications

EAN: 5055387668119, Colour: White

UPC: 796435 44 726 7, Colour: White



### Ekran ve görüntü

Görüntü Teknolojisi	DLP™
Doğal Çözünürlük	WXGA (1280x800)
Parlaklık (Lümen)	4.000
Kontrast Oranı	300.000
Doğal en boy oranı	16:10
Desteklenen en-boy oranı	4:3,16:9,16:10
Keystone Düzeltme (Yatay)	+/-5°
Keystone Düzeltme (Dikey)	+/-5°
Görüntülenebilir Renkler (Milyonlar)	1073.4
Yatay Tarama Hızı (hz)	15 ~ 140
Dikey Tarama Hızı (Hz)	24 ~ 120
Uniformity (Yüzde)	75
Ekran boyutu	2.03m ~ 3.3m (80" ~ 130") diagonal

### Lamba bilgisi

Işık Kaynağı	DuraCore Lazer
ProjelerSaati	30.000

### Optik

Atma oranı	0.266:1
ProjeksiyonMesafeMetre	0.202m - 0.398m
SabitLensOdak Uzunluğu	3.72mm/0.146"
Doğal offset	116%

### bağlantı

Bağlantılar	<b>Inputs</b> 2 x HDMI 1.4b <b>Outputs</b> 1 x USB-A gücü 1.5A, 1 x Ses 3,5 mm <b>Control</b> 1 x RS232, 1 x RJ45
-------------	---

### Genel

Gürültü Düzeyi Tipik (Db)	27
Gürültü Seviyesi Max (Db)	34
Bilgisayar Uyumluluğu	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
3D Uyumluluk	Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D)
Proj3DType	Full 3D
Ürün Güvenliği	Security bar, Kensington Lock, Password protected interface
IP derecelendirme	IP6X
OSDLang'lar	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
7/24 işlem	Yes
360 derece işlem	Yes
Çalışma koşulları	5°C~40°C, max altitude 10,000ft
Uzaktan kumanda	Kart stili
Isı Yayımı (Btu / Saat)	691
Hoparlör Sayısı	1
Hoparlör Watt	15
Kutuda	AC power cord Remote control 1x CR2025 Battery Basic user manual

### ağ

LanControl	Yes
LAN(DHCP)	Yes

### Güç

Güç kaynağı	External power supply, 180W DC 19.5V, 9.23A
Güç Tüketimi / Watt (Beklemede)	<0.5
Güç Tüketimi / Watt (Min)	119
Güç Tüketimi / Watt (Maks)	173

### Ağırlık ve boyutlar

Ürün Boyutları	327 x 327 x 109
Brüt ağırlık	3.9 kg
Net ağırlığı	6.08 kg

