CUTTING-EDGE INTEGRATED 36" MFP WITH GLOBAL SCANNING SCANAPP LEI SOFTWARE



- Save time by printing and scanning simultaneously
 double efficiency from parallel processing
- High-quality printing with rich colour and sharp text from 5-colour, full pigment Lucia TD ink
- Streamlined internal operations, including dampened fans and vibrations, means 60% less noise
- With ScanApp Lei software, easily save scanned data directly to USB, with TIFF, PDF and JPEG file formats supported
- A compact and integrated design, with full front usability, means little installation space
- SingleSensor technology from Global Scanning delivers crystal clear lines and text as well as bold colours
- Perfect for indoor and outdoor applications including a unique Water Resistant Media portfolio
- Ease of use can be reached by the 3-inch flat panel touchscreen display

Easy to use, the imagePROGRAF TM-300 MFP L36ei prints up to 144 pph (A1) and simultaneously processes printing and scanning to save more time. Dedicated ScanApp Lei software boosts productivity with continuous scan and copy to cloud, USB and PC.



PRODUCT RANGE



TM-300



TM-300 MFP T36



TM-305 MFP T36



TECHNICAL SPECIFICATIONS

SCANNER TECHNOLOGY

Scan technology Optical resolution Scan speed

SingleSensor with multiple LED illumination

COPY 300/300dpi Draft = 1ips colour, 3ips mono 300/600dpi Standard = 1ips colour, 3ips mono 600/600dpi Best = 0.5ips colour, 1.5ips mono

Scan modes

Scan to USB - RGB/Greyscale/BW, TIFF (No ScanApp Lei) Scan to USB - RGB/Greyscale/BW, JPG, PDF, PDF/A, M-PDF (ScanApp Lei available) Scan to PC - RGB/Greyscale/BW, Tiff, JPEG, PDF, PDF/A, TiffG4, M-PDF

TiffG4, M-PDF Copy - RGB/Greyscale/BW Copy & Archive -(Combination of Copy and Scan to PC above). Cloud connectivity is achieved by a link to Canon's Direct

Paper Path

Max. scan width Min. scan width 6" / 152.4mm Max. document width 38" / 965.2mm

Max. scan length Max. & Min. document thickness

Scan to USB

Scan to Network - ScanApp Lei

Languages for ScanApp Lei

Control panel Weight of scanner

Dimensions width Dimensions height Dimension depth

Power supply

Max. power consumption

Acoustic noise levels

Environmental

Compliances What's in the box?

PRINTER TECHNOLOGY

Print Technology

Print Resolution

Printer Type

Number of Nozzles

Line Accuracy Nozzle Pitch Ink Droplet Size

FINE

Ink Capacity





600dpi

SCAN 200dpi Draft = 1ips colour, 3ips mono 300dpi Standard = 0.5ips colour, 1.5ips mono 600dpi Best = 0.33ips colour, 1ips mono

Print & Share. PRINT is achieved by using Canon's Direct Print & Share. Face up, rear exit. Forward document transport only Document return guide(s) included

36" / 914.4mm

109" / 2768mm

Designed to scan Canon iPF printer CAD paper. Max = 0.5mm

Accuracy 0.2% +/-1 pixel USB2, 128GB FAT32.

ScanApp Lei - Sets scan directory.

Minimum PC specification: • Windows 7/8/10 - 32bit.

• 100Mbs Ethernet • Intel Celeron, Core-Duo, Core-2-Duo or

2.8GH2 Hyper-Threading (HT) or AMD Dual-Core processors

• 2GB RAM • High speed 7,200rpm Serial ATA

(SATA) HDD with minimum 2GB for applications and 20GB

(SATA) HDD with minimum 2GB for applications and 20GB free for images.

Suggested PC specification: • Windows 7/8/10 - 64bit. • GB Ethernet. • Intel 3,15 or 17 processors • 4GB RAM • High speed 7,20 prom Serial ATA (SATA) HDD with minimum 2GB for applications and 20GB free for images.

English/French/German/Italian/Spanish/Simplified Chinese/Traditional Chinese/Korean/Russian/Portuguese/ Japanese/Czech/Polish

3" touch screen display

6.56kg (14.5lbs) without Doc return guide 1238mm

Without Doc Return Guide - Paper tray folded: 146mm Without Doc Return Guide - Paper Tray flat: 193mm With Doc Return Guide - Paper tray folded: 206mm With Doc Return Guide - Paper Tray flat: 253mm

External PSU: Input: 100 - 240V, 50-60Hz Output: 3.42A at 19V.

Standby (sleep): 0.6W Idle: 11.7W Scanning: 17.5W Temp: 10-35C Humidity: 10-90% 50.6dB gray scan

Europe : CE mark, Russia : EAC, Other countries : CB

CD for ScanApp Lei software and PDF documentation: L36ei Scanner User Manual per language and Quick Start

Guide. L36ei Scanner Quick Start Guide. Ethernet cable (2 meter)

5 Colour 36"/914mm

Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head \times 1 print head) 2.400 x 1.200 dpi

15.360 nozzles (MBK 5.120 nozzles, Other Colours 2.560

+0.1% or less 1.200 dpi (2 lines)

minimum 5 pl per colour

Sales Ink: 130ml/300ml Bundled Starter Ink: 130ml (Matte Black)/90ml (Black, Cyan, Magenta, Yellow)

Ink Type Pigment inks - Black, Matte Black, Cyan, Magenta, Yellow OS Compatability

imagePROGRAF

Microsoft Windows 32 Bit: Windows 7, 8.1, 10, 64 Bit: Windows 7, 8.1, 10, Server 2008R2, Server 2012/2012R2, Server 2016 Apple Macintosh: OS X 10.10.5 - OS X 10.11, macOS 10.13

SG Raster (Swift Graphic Raster), HP-GL/2, HP RTL, JPEG (Ver. JFIF 1.02)

TM-300 MFP L36ei

USB B Port: Built-in Hi-Speed USB Ethernet: IEEE 802.3 10-base-T/IEEE 802.3u 100base-TX/ IEEE 802.3ab 1000base-T/IEEE 802.3x Full Duplex Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b

MEMORY Standard memory 2GB

PRINTING SPEED

Standard Interfaces

CAD Drawing:

Plain Paper (A0 Roll)

Poster: Plain Paper (AO Roll)

Heavy Coated Paper (A0 Roll)

MEDIA HANDLING Media Feed and Output

Media Thickness

Minimum Printable Length

Maximum Printable Length

Maximum Media Roll Diameter Media Core Size

Margins Recommended area

Margins Printable area

Media Feed Capacity Borderless Printing Width (Roll Only)

Maximum number of delivered

What's in the Box?

Software Included Optional Items

Europe : CE mark, Russia : EAC, Other countrie Certification L36ei scanner Printer mounting brackets, fixings & 3mm tool 2 feet for desktop use 2 paper edge guides 3 Document return guides Calibration target

Power Supply Regional - Mains power cord(s) (2 meter)

CONSUMABLES User Replaceable Items

0:40 (Fast Economy Mode)

0:46 (Fast) 1:14 (Standard)

0:44 (Fast) 1:18 (Standard) 1:41 (Fast) 2:36 (Standard)

Roll paper: One Roll, Uppper-loading, Front Output Cut sheet: Upper-loading, Front Output (Manual feed using media locking lever) Roll paper: 203.2 - 917 mm Cut sheet: 203.2 - 917 mm

Roll/Cut: 0.07 - 0.8 mm

Roll paper: 203.2 mm Cut sheet: 279.4 mm (Varies according to the OS and application) Cut sheet: 1.6 m

Internal diameter of roll core: 2"/3"

Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm

Roll paper: Top: 3 mm, Bottom: 3 mm, Side: 3 mm Roll paper (borderless): Top: 0 mm, Bottom: 0 mm, Side: 0 mm Cut sheet for Apple AirPrint Only: Top: 3 mm, Bottom: 12.7 mm, Side: 3 mm Cut sheet for thers: Top: 3 mm, Bottom: 20 mm, Side: 3 mm

Manually switchable by user

Sistem (JIS B2), 728mm (BIS B1), 594mm (ISO A1), 84lmm (ISO A0), 10", 14", 17", 24", 36" [Printable] 257mm (JIS B4), 297mm (ISO A3), 329mm (ISO A3+), 420mm (ISO A2), 8", 12", 16", 20", 30", 300mm, 500mm, 600mm, 800mm

SD-32 Stand/Basket - Standard position: 1 sheet SD-32 Stand/Basket - Flat position: 20 sheets on A1, A2 landscape (3)

Printer, printer stand: SD-32, 1 x print head, 3-inch paper core attachment, Power Cable, UK Power cord (240V,3P), 1 set of starter ink tanks, Set up guide, Safety/Standard Environment leaflet User software CD-ROM (Win)
PosterArtist Lite CD-ROM, EU Biocide Sheet, Eurasian Economic Union Sheet, Important Information Sheet

imagePROGRAF TM-Series Printer Driver, Print Plug-In for Office, Quick Utility Toolbox and PosterArtist Lite Other software available as Download from Web.

2/3" Roll Holder: RH2-35

Ink Tank: PFI-120 (130ml), PFI-320 (300ml) Print Head: PF-06 Cutter Blade: CT-08 Maintenance Cartridge: MC-31

Footnotes

Maximum number of supported printers or PCs running ScanApp Lei = 15 (Maximum number that can be assigned a number = 9). Note 1

Scanner is manufactured by UK based company, Global Scanning

Note 3 Excludes strong curl conditions

Disclaimer

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice." and All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended

> Canon Inc. canon.com Canon Europe

canon-europe.com

English edition © Canon Europa N.V.,2018

